DUPLI-COLOR Galvinol

Ord.-no.: 334337, 334344

Technical Information



Special primer improving the adhesion on very smooth and non-porous surfaces. Remains sticky at the surface and forms the perfect adhesion promoter for the subsequent painting with DUPLI-COLOR Alkyton RUST PROTECTION.

Quality & properties

- Solvent containing special primer
- For brush application
- Forms a sticky surface as adhesion promoter

Physical & chemical data

- Base: Acrylic resin
- Colourname: transparent
- Smell: Characteristic
- Minimum Working Temperature: 5 °C
- Maximum Working Temperature: 35 °C
- Vapour pressure: 97/20 bar
- Flash point: -4 °C
- Relative density: 0.87
- Storage stability: 5 y
- Content:
  - 250 ML
  - 750 ML

How to use

- Remove oil, grease and all other surface contaminations by alkaline or high pressure (steam), cleaning in combination with appropriate detergents. Remove previous coatings completely. Use depending on necessity a wire brush, sand blasting or sand paper. The surface must be clean and dry during application.
- To ensure homogeneity, the lacquer should be thoroughly stirred prior to use.
- DUPLI-COLOR GALVINOL Special Primer is intended for brush application. Application by air-atomised spraying or airless spraying is not recommended. Use natural bristles, long hair brushes.
- Apply the primer in very thin uniform layers.
- Apply in well-ventilated areas.
- During application the surrounding area, the substrate and the adhesion primer should have a temperature above 5°C and below 35°C.
- Apply the top coat earliest after 30 minutes, but within 24 hours. The longer you wait, the bigger the risk to include particles of dust and dirt in the sticky surface.
- Cleanup: Use white spirit
- Application conditions: Temperature of air, substrate and coating material: between 5° and 35 °C Relative air humidity: below 85 % Substrate temperature: at least 3°C above dew point.

Environmentally sound
European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal
Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling
All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of August 18, 2022 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - info-nl@european-aerosols.com